



FM Electrical Supplies Australia Pty Ltd



Contact: sales@fmes.com.au

bob. c.a./ a.c. coil

GH15RFT1.3.00

GH15RFT2.3.00

GH15RFT3B.3.00

GH15RFT4.3.00

GH15RFT5.3.00

GH15RFT6.3.00

GH15RFT8.3.00

GH15RFT10.3.00

AC-6b

Potenza nominale ≤ 55°C

Rated power ≤ 55°C

In LINE

220-240V [KVAR]

7,5

10

15

20

25

30

40

50

380-415V [KVAR]

15

25

30

40

50

60

80

100

440V [KVAR]

15

27,5

33

44

56

68

88

110

500V [KVAR]

15

27,5

33

44

56

68

88

110

690V [KVAR]

20

40

50

66

80

95

125

160

Inside DELTA

220-240V [KVAR]

20

40

50

66

80

95

125

160

380-415V [KVAR]

20

40

50

66

80

95

125

160

Dimensioni di ingombro e peso
Overall dimensions and weight

(lxhxp)
(wxhxd)

[mm] [kg]

45x80x122
■ 0,51

45x80x128
■ 0,53

45x110x128
■ 0,56

60x114x146
■ 1,20

79x137x167
■ 1,20

79x162x167
■ 2,00

Fissaggio / Fixing

Viti o DIN 35mm / Screws or DIN 35mm

Viti / screws

Grado di protezione / Protection degree

IP20

IP20 frontale / IP20 frontal

Temperatura funzionamento / Working temp.

[°C]

-25°C +55°C

AC-6b Durata elettrica
Electrical durability

Ue ≤440V

in line [10³ op]

500

400

250

150

135

135

inside delta [10³ op]

300

240

150

Frequenza max manovre
Max frequency of load operations

[op/h]

250

120

Corrente max di picco / Max peak current

[kA]

illimitata / unlimited

Tensione nominale d'isolamento
Rated insulation voltage

[V]

690

Fusibili di protezione contro cortocircuito
Coordinamento Tipo 1 IEC 60947-4-1
Short circuit protection fuses - Type 1 coord

gG - Ue ≤ 440V [A]

40

63

80

100

125

160

200

250

Tensioni nominali / Rated control voltage

c.a. / a.c. 50-60Hz

12...690V - disponibili su richiesta versioni DC / if required, D.C. version available

Assorbimento medio

spunto / pick-up [VA]

80...100

250

Average coil consumption

spunto / pick-up [VA/W]

9...12 / 4

18 / 6

Contatti ausiliari / auxiliary contacts

laterale / side mounting

GH15S11 (1NO+1NC)

frontale / top mounting

GH15T01 (1NC) - GH15T10 (1NO)

PER MAGGIORI INFORMAZIONI: contattare l'ufficio commerciale / FOR MORE INFO: please contact our commercial dept.